







The DS40 delievers 4"x6" photos in just 8 seconds.



Giving flexibility on photo formats, the DS40 offers anything from 4"x6" to 6"x8".



Print method	Dye-sublimation thermal transfer method		
Print mode	•	High-speed mode	High-resolution mode
Resolution		300x300dpi	300x600dpi
Print size	2"x6" 2 up*	•	•
	4"x6"		
	5"x7"		
	6"x8"		
Print number	4"x6"	400 sheets	
	5"x7"	200 sheets	
	6"x8"	200 sheets	
Print speed	4"x6"	8.9sec.	11.7sec.
·	5"x7"	12.8sec.	17.4sec.
	6"x8"	13.9sec.	19.3sec.
Finishing options	Glossy, matte		
Ribbon finish	YMC + overcoat		
Interface	USB 2.0 (Maximum 480Mbps)		
Driver software	Windows® 2000 / XP / VISTA / Windows 7 & 8 - MAC OS		
External dimensions	12.7"Wx14.4"Dx6.7"H		
Weight (Excluding accessories and media) Approx. 30 lbs			
Power supply	AC100V ~ 240V 50/60 HZ		
Power consumption (when printing)	100V 3.96A 240V 1.69A		
Accessories	Power supply cord		
Media	DS404x6, DS405x7A, DS406x8		

^{*}When two 2x6" size is printed using 4x6" media.



Many thousands of printers are performing reliably in the field for a number of years.



On the same photo paper, the DS40 produces media in glossy or matte according to your requirements.

















